




Tesisat Kabloları Installation Cables

PVC Yalıtkanlı ve Kılıflı Bükülgen Kablolar 300/300V PVC Insulated, Sheated, Flexible Cables 300/300V



H03VV-F 300/300V
218Y FLEXIBLE CABLE

Standartlar / Standards

TS 9760 HD 21.5 S3
VDE 0281-5
BS 6500

Kullanım Alanı

Orta büyüklükte mekanik zorlamaların olduğu tesislerde, kuru veya ıslak yerlerde, taşınabilir cihazlarda (buzdolabı, çamaşır makinesi v.s), sabit cihazların hareketli aksamalarında veya hareketli cihazlarda.

Yapı

İletken: İnce Çok Telli Bakır (Class 5 - Esnek Bükülü Bakır)
İzolasyon: CIDEX - PVC Yalıtkan
Dolgu: PVC Dolgu
Kılıf: CABON - PVC Kılıf
Maks. İşletme Sıcaklığı: 70°C
Kısa devre sıcaklığı: 160°C
Test gerilimi: (AC) 2kV

Used In

In dry and covered places, in medium size plants having very little mechanical pressures, in domestic premises as mobile connection and light duty cable. For use with light portable appliances such as radios, table lamps and office machines.

Construction

Conductor: Fine Stranded Copper (Class 5 - Flexible Plain Copper)
Insulation: CIDEX - PVC Insulation
Filler: PVC Filler
Sheath: CABON - PVC Sheath
Max. Operating Temperature: 70°C
Short Circuit Temperature: 160°C
Testing Voltage: (AC) 2kV

Nominal Kesit Rated Cross Section mm ²	Nominal Dış Çap (yaklaşık) Overall diameter (approx.) mm	Net Ağırlık (yaklaşık) Net Weight (approx.) kg/km	İletkenin max. 20° C DC Direnci Conductor DC resistance at 20° C Ω / km
H03VV-F - Cu/PVC/PVC			
2 x 0,50	5	38	39
2 x 0,75	5,3	46	26
3 x 0,50	5,3	45	39
3 x 0,75	5,6	56	26
4 x 0,50	5,6	55	39
4 x 0,75	5,9	70	26