



Tesisat Kabloları Installation Cables

PVC Yalıtkanlı ve Kılıflı Çok Damarlı Bükülgen Yassı Kablolar PVC Insulated, Sheated, Multi Core Flat Flexible Cables

H03VVH2-F 300/500V
2192Y FLEXIBLE CABLE

Standartlar / Standards

TS 9760 HD 21.5 S3
VDE 0281-5
BS 6500



Kullanım Alanı

Orta büyüklükte mekanik zorlamanın az olduğu tesislerde, kuru, kapalı yerlerde hareketli bağlantı kablosu olarak kullanılırlar.

Yapı

İletken: İnce Çok Tellî Bakır (Class 5 - Esnek Bükülü Bakır)
İzolasyon: CIDEX - PVC Yalıtkan
Dolgu: PVC Dolgu
Kılıf: CABON - PVC Kılıf
Maks. İşletme Sıcaklığı: 70°C
Kısa devre sıcaklığı: 160°C
Test gerilimi: (AC) 2kV

Used In

In dry and covered places, in medium size plants having very little mechanical pressures, as mobile connection and indoor general wiring cable.

Construction

Conductor: Fine Stranded Copper (Class 5 - Flexible Plain Copper)
Insulation: CIDEX - PVC Insulation
Filler: PVC Filler
Sheath: CABON - PVC Sheath
Max. Operating Temperature: 70°C
Short Circuit Temperature: 160°C
Testing Voltage: (AC) 2kV

Nominal Kesit Rated Cross Section mm ²	Nominal Dış Çap (yaklaşık) Overall diameter (approx.) mm	Net Ağırlık (yaklaşık) Net Weight (approx.) kg/km	İletkenin max. 20° C DC Direnci Conductor DC resistance at 20° C Ω / km
H03VVH2-F - Cu/PVC(xlpe)/PVC			
2 x 0,50	3,1 x 5,0	31	39
2 x 0,75	3,3 x 5,4	37	26

ISO 9000 - ISO 14000 - ISO 18000 - TSE

H03VVH2-F / 2192Y